



The first choice of customers in various industries

- Sewage treatment
- Chemical industry
- Thermal power plant
- Cement industry
- Food industry
- Paper Industry

Pharmaceutical industry And many other industries

Application area

- .Water and wastewater treatment
- .Aeration
- .Filter backwash
- .Pneumatic conveying of bulk materials
- .Gas delivery
- .Desulfurization and denitrification
- .Textile process
- And many other fields

Host model	LBG115RA	Intake pressure	1 atm	IAT	25°C	AT	80%R. H.	
DISCHARGE (bar)	RPM	type	CC		Shaft power (kW)	EGT °C	FTT °C	Injection pressure bar
			(m³/h)	(m3/min)				
0.4~0.9 (bar)	3500	I	209.1~195.1	3.5~3.3	5.4~8.7	67.6~107.2	65	0.5~1.0
	3750		231.0~215.5	3.8~3.6	5.8~9.2	66.3~105.1	65	0.5~1.0
	4000		254.0~237.0	4.2~4.0	6.1~9.7	65.0~103.0	65	0.5~1.0
	4250		275.3~256.8	4.6~4.3	6.5~10.3	64.7~102.5	65	0.5~1.0
	4500		297.3~277.4	5.0~4.6	6.9~10.9	64.4~102.0	65	0.5~1.0
	4750		321.7~300.1	5.4~5.0	7.2~11.5	64.0~101.5	65	0.5~1.0
	5000		345.4~322.2	5.8~5.4	7.7~12.2	63.7~101.0	65	0.5~1.0
	5250		368.1~343.4	6.1~5.7	8.2~13.0	63.4~100.5	65	0.5~1.0
	5500		391.4~365.2	6.5~6.1	8.6~13.7	63.1~99.9	65	0.5~1.0
	5750		415.3~387.5	6.9~6.5	9.1~14.5	62.8~99.4	65	0.5~1.0
6000	439.9~410.4	7.3~6.8	9.6~15.3	62.1~98.5	65	0.5~1.0		
1~1.5 (bar)	3500	π	192.6~180.3	3.2~3.0	9.5~13.0	115.5~164.4	65	0.5~1.0
	3750		212.8~199.2	3.5~3.3	10.0~13.8	113.2~161.2	65	0.5~1.0
	4000		234.0~219.0	3.9~3.7	10.6~14.6	111.0~158.0	65	0.5~1.0
	4250		253.6~237.3	4.2~4.0	11.3~15.5	110.4~157.2	65	0.5~1.0
	4500		273.9~256.3	4.6~4.3	11.9~16.4	109.9~156.4	65	0.5~1.0
	4750		296.3~277.3	4.9~4.6	12.6~17.3	109.3~155.6	65	0.5~1.0
	5000		318.2~297.8	5.3~5.0	13.4~18.4	108.8~154.9	65	0.5~1.0
	5250		339.1~317.3	5.7~5.3	14.2~19.5	108.3~154.1	65	0.5~1.0
	5500		360.6~337.4	6.0~5.6	15.0~20.7	107.7~153.3	65	0.5~1.0
	5750		382.6~358.1	6.4~6.0	15.9~21.8	107.2~152.6	65	0.5~1.0
6000	405.2~379.2	6.8~6.3	16.7~23.0	106.1~151.0	65	0.5~1.0		

Host model	LBG115RB	Intake pressure	1 atm	IAT	25°C	AT	80%R. H.	
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure
			(m³/h)	(m³/min)	(kW)	°C	°C	bar
0.4~0.9 (bar)	3500	I	297.8~269.5	5.0~4.5	7.4~11.0	71.8~104.0	65	0.5~1.0
	3750		327.2~296.2	5.5~4.9	7.9~11.6	70.4~1020	65	0.5~1.0
	4000		358.0~324.0	6.0~5.4	8.3~12.3	69.0~100.0	65	0.5~1.0
	4250		388.0~351.1	6.5~5.9	8.9~13.1	68.7~99.5	65	0.5~1.0
	4500		419.0~379.2	7.0~6.3	9.4~14.0	68.3~99.0	65	0.5~1.0
	4750		453.4~410.3	7.6~6.8	10.1~14.9	68.0~98.5	65	0.5~1.0
	5000		486.8~440.5	8.1~7.3	10.7~15.8	67.6~98.0	65	0.5~1.0
	5250		521.3~471.8	8.7~7.9	11.3~16.8	67.3~97.5	65	0.5~1.0
	5500		557.1~504.2	9.3~8.4	12.0~17.8	67.0~97.0	65	0.5~1.0
	5750		594.0~537.6	9.9~9.0	12.7~18.8	66.6~96.6	65	0.5~1.0
	6000		632.3~572.2	10.5~9.5	13.3~19.8	66.0~95.6	65	0.5~1.0
	1~1.5 (bar)		3500	II	264.5~242.1	4.4~4.0	11.7~15.4	112.4~161.3
3750		290.7~266.0	4.8~4.4		12.4~16.4	110.2~158.1	65	0.5~1.0
4000		318.0~291.0	5.3~4.9		13.1~17.3	108.0~155.0	65	0.5~1.0
4250		344.6~315.4	5.7~5.3		14.0~18.5	107.5~154.2	65	0.5~1.0
4500		372.2~340.6	6.2~5.7		14.9~19.7	106.9~153.5	65	0.5~1.0
4750		402.7~368.5	6.7~6.1		15.9~21.0	106.4~152.7	65	0.5~1.0
5000		432.4~395.7	7.2~6.6		16.9~22.3	105.9~151.9	65	0.5~1.0
5250		463.1~423.8	7.7~7.1		17.9~23.6	105.3~151.2	65	0.5~1.0
5500		494.8~452.8	8.2~7.5		18.9~25.0	104.8~150.4	65	0.5~1.0
5750		527.7~482.9	8.8~8.0		20.0~26.4	104.3~149.7	65	0.5~1.0
6000		561.6~513.9	9.4~8.6		21.1~27.8	103.2~148.2	65	0.5~1.0

Host model	LBG170RA	Intake pressure	1 atm	IAT	25°C	AT	80%R. H.			
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure		
			(m³/h)	(m³/min)	(kW)	°C	°C	bar		
0.4~0.9 (bar)	2400	I	595.8~578.1	9.9~9.6	13.3~21.2	73.2~109.3	65	0.7~1.2		
	2600		652.7~633.3	10.9~10.6	14.2~22.7	72.1~107.7	65	0.7~1.2		
	2800		711.4~690.3	11.9~11.5	15.2~24.2	71.1~106.1	65	0.7~1.2		
	3000		772.0~749.0	12.9~12.5	16.1~25.7	70.0~104.5	65	0.7~1.2		
	3200		831.6~806.8	13.9~13.4	17.1~27.4	69.1~103.1	65	0.7~1.2		
	3400		892.6~866.0	14.9~14.4	18.2~29.0	68.2~101.8	65	0.7~1.2		
	3600		955.2~926.8	15.9~15.4	19.2~30.7	67.3~100.5	65	0.7~1.2		
	3800		1019.4~989.0	17.0~16.5	20.3~32.4	66.4~99.2	65	0.7~1.2		
	4000		1085.1~1052.8	18.1~17.5	21.3~34.1	66.1~98.7	65	0.7~1.2		
	4200		1152.5~1118.1	19.2~18.6	22.4~35.7	65.8~98.2	65	0.7~1.2		
	4400		1221.5~1185.1	20.4~19.8	23.4~37.4	65.4~97.7	65	0.7~1.2		
	4600		1292.2~1253.7	21.5~20.9	24.5~39.1	65.1~97.2	65	0.7~1.2		
	4800		1364.6~1324.0	22.7~22.1	25.5~40.7	64.8~96.7	65	0.7~1.2		
	5000		1438.8~1395.9	24.0~23.3	26.6~42.4	64.5~96.2	65	0.7~1.2		
	1~1.5 (bar)		I类2800以下 不推荐使用	II	575.0~562.6	9.6~9.4	23.0~33.6	116.1~152.1	65	0.7~1.2
			2800		629.9~616.4	10.5~10.3	24.7~36.0	114.4~149.9	65	0.7~1.2
3000		686.6~671.8	11.4~11.2		26.3~38.3	112.7~147.7	65	0.7~1.2		
3200		745.0~729.0	12.4~12.2		27.9~40.7	111.0~145.5	65	0.7~1.2		
3400		802.5~785.3	13.4~13.1		29.7~43.3	109.6~143.6	65	0.7~1.2		
3600		861.4~842.9	14.4~14.0		31.5~46.0	108.1~141.7	65	0.7~1.2		
3800		921.8~902.0	15.4~15.0		33.3~48.6	106.7~139.9	65	0.7~1.2		
4000		983.7~962.6	16.4~16.0		35.2~51.3	105.3~138.1	65	0.7~1.2		
4200		1047.2~1024.7	17.5~17.1		37.0~54.0	104.8~137.4	65	0.7~1.2		
4400		1112.2~1088.3	18.5~18.1		38.8~56.6	104.3~136.7	65	0.7~1.2		
4600		1178.8~1153.5	19.6~19.2		40.6~59.2	103.8~136.0	65	0.7~1.2		
4800		1247.0~1220.2	20.8~20.3		42.4~61.8	103.2~135.3	65	0.7~1.2		
5000		1316.9~1288.6	21.9~21.5		44.2~64.5	102.7~134.7	65	0.7~1.2		
5000		1388.5~1358.6	23.1~22.6		46.0~67.1	102.2~134.0	65	0.7~1.2		

PARAMETERS

Host model	LBG170RB	Intake pressure	1 atm	IAT	25℃	AT	80%R. H.			
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure		
			(m³/h)	(m³/min)	(kW)	℃	℃	bar		
0.4~0.9 (bar)	2400	I	801.9~785.7	13.4~13.1	16.5~26.2	73.2~109.3	65	0.7~1.2		
	2600		878.5~860.7	14.6~14.3	17.7~28.1	72.1~107.7	65	0.7~1.2		
	2800		957.5~938.2	16.0~15.6	18.8~30.0	71.1~106.1	65	0.7~1.2		
	3000		1039.0~1018.0	17.3~17.0	20.0~31.8	70.0~104.5	65	0.7~1.2		
	3200		1119.2~1096.6	18.7~18.3	21.3~33.9	69.1~103.1	65	0.7~1.2		
	3400		1201.4~1177.1	20.0~19.6	22.6~35.9	68.2~101.8	65	0.7~1.2		
	3600		1285.6~1259.6	21.4~21.0	23.9~38.0	67.3~100.5	65	0.7~1.2		
	3800		1371.9~1344.2	22.9~22.4	25.2~40.1	66.4~99.2	65	0.7~1.2		
	4000		1460.4~1430.9	24.3~23.8	26.5~42.1	66.1~98.7	65	0.7~1.2		
	4200		1551.1~1519.7	25.9~25.3	27.8~44.2	65.8~98.2	65	0.7~1.2		
	4400		1644.0~1610.7	27.4~26.8	29.1~46.2	65.4~97.7	65	0.7~1.2		
	4600		1739.1~1704.0	29.0~28.4	30.4~48.3	65.1~97.2	65	0.7~1.2		
	4800		1836.6~1799.4	30.6~30.0	31.7~50.3	64.8~96.7	65	0.7~1.2		
	5000		1936.4~1897.2	32.3~31.6	33.0~52.4	64.5~96.2	65	0.7~1.2		
	1~1.5 (bar)		II类2800以下 不推荐使用	II	782.6~767.9	13.0~12.8	28.9~42.7	116.1~152.1	65	0.7~1.2
			857.3~841.3		14.3~14.0	30.9~45.8	114.4~149.9	65	0.7~1.2	
2800		934.5~917.0	15.6~15.3		33.0~48.8	112.7~147.7	65	0.7~1.2		
3000		1014.0~995.0	16.9~16.6		35.0~51.8	111.0~145.5	65	0.7~1.2		
3200		1092.2~1071.8	18.2~17.9		37.3~55.1	109.6~143.6	65	0.7~1.2		
3400		1172.5~1150.5	19.5~19.2		39.5~58.5	108.1~141.7	65	0.7~1.2		
3600		1254.7~1231.2	20.9~20.5		41.8~61.9	106.7~139.9	65	0.7~1.2		
3800		1338.9~1313.8	22.3~21.9		44.1~65.3	105.3~138.1	65	0.7~1.2		
4000		1425.3~1398.6	23.8~23.3		46.4~68.6	104.8~137.4	65	0.7~1.2		
4200		1513.8~1485.4	25.2~24.8		48.6~71.9	104.3~136.7	65	0.7~1.2		
4400		1604.4~1574.3	26.7~26.2		50.9~75.3	103.8~136.0	65	0.7~1.2		
4600		1697.3~1665.5	28.3~27.8		53.1~78.6	103.2~135.3	65	0.7~1.2		
4800		1792.4~1758.8	29.9~29.3		55.4~82.0	102.7~134.7	65	0.7~1.2		

Host model	LBG210RA	Intake pressure	1 atm	IAT	25℃	AT	80%R. H.			
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure		
			(m³/h)	(m³/min)	(kW)	℃	℃	bar		
0.4~0.9 (bar)	2200	I	1190.9~1158.5	19.8~19.3	24.6~35.4	78.6~112.0	65	0.7~1.2		
	2400		1314.9~1279.2	21.9~21.3	26.5~38.2	77.5~110.4	65	0.7~1.2		
	2600		1441.8~1402.6	24.0~23.4	28.5~41.0	76.3~108.8	65	0.7~1.2		
	2800		1571.6~1528.9	26.2~25.5	30.3~43.7	75.2~107.1	65	0.7~1.2		
	3000		1704.3~1658.0	28.4~27.6	32.2~46.4	74.1~105.6	65	0.7~1.2		
	3200		1840.0~1790.0	30.7~29.8	34.0~49.0	73.0~104.0	65	0.7~1.2		
	3400		1961.8~1908.5	32.7~31.8	36.1~52.1	72.1~102.6	65	0.7~1.2		
	3600		2084.5~2027.9	34.7~33.8	38.3~55.1	71.1~101.3	65	0.7~1.2		
	3800		2208.0~2148.0	36.8~35.8	40.4~58.2	70.2~100.0	65	0.7~1.2		
	4000		2332.4~2269.0	38.9~37.8	42.5~61.3	69.3~98.7	65	0.7~1.2		
	4200		2457.6~2390.8	41.0~39.8	44.6~64.3	68.9~98.2	65	0.7~1.2		
	4400		2583.6~2513.4	43.1~41.9	46.8~67.4	68.6~97.7	65	0.7~1.2		
	4600		2710.5~2636.8	45.2~43.9	48.9~70.4	68.2~97.2	65	0.7~1.2		
	4800		2838.2~2761.1	47.3~46.0	51.0~73.5	67.6~96.3	65	0.7~1.2		
	1~1.5 (bar)		12bar以上 不推荐低速	II	1152.1~1103.5	19.2~18.4	37.9~52.0	121.7~154.1	65	0.7~1.2
			2600		1272.1~1218.5	21.2~20.3	41.0~56.2	119.9~151.8	65	0.7~1.2
2800		1394.8~1336.0	23.2~22.3		43.9~60.3	118.2~149.5	65	0.7~1.2		
3000		1520.3~1456.3	25.3~24.3		46.9~64.3	116.4~147.3	65	0.7~1.2		
3200		1648.7~1579.3	27.5~26.3		49.7~68.2	114.7~145.1	65	0.7~1.2		
3400		1780.0~1705.0	29.7~28.4		52.5~72.0	113.0~143.0	65	0.7~1.2		
3600		1897.9~1817.9	31.6~30.3		55.8~76.5	111.5~141.1	65	0.7~1.2		
3800		2016.5~1931.6	33.6~32.2		59.1~81.0	110.1~139.3	65	0.7~1.2		
4000		2136.0~2046.0	35.6~34.1		62.3~85.5	108.7~137.5	65	0.7~1.2		
4200		2256.3~2161.2	37.6~36.0		65.6~90.0	107.2~135.7	65	0.7~1.2		
4400		2377.4~2277.2	39.6~38.0		68.9~94.5	106.7~135.0	65	0.7~1.2		
4600		2499.3~2394.0	41.7~39.9		72.2~99.0	106.2~134.4	65	0.7~1.2		
4800		2622.1~2511.6	43.7~41.9		75.5~99.0	105.6~133.7	65	0.7~1.2		
4800		2745.7~2630.0	45.8~43.8		78.8~108.0	104.6~132.3	65	0.7~1.2		

PARAMETERS

Host model	LBG210RB	Intake pressure	1 atm	IAT	25°C	AT	80%R. H.			
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure		
			(m³/h)	(m³/min)	(kW)	°C	°C	bar		
0.4~0.9 (bar)	2200	I	1469.2~1436.8	24.5~23.9	29.6~44.1	78.6~112.0	65	0.7~1.2		
	2400		1622.2~1586.5	27.0~26.4	32.0~47.6	77.5~110.4	65	0.7~1.2		
	2600		1778.8~1739.6	29.6~29.0	34.3~51.1	76.3~108.8	65	0.7~1.2		
	2800		1938.9~1896.2	32.3~31.6	36.6~54.4	75.2~107.1	65	0.7~1.2		
	3000		2102.6~2056.3	35.0~34.3	38.8~57.8	74.1~105.6	65	0.7~1.2		
	3200		2270.0~2220.0	37.8~37.0	41.0~61.0	73.0~104.0	65	0.7~1.2		
	3400		2419.1~2365.8	40.3~39.4	43.6~64.8	72.1~102.6	65	0.7~1.2		
	3600		2569.1~2512.5	42.8~41.9	46.1~68.6	71.1~101.3	65	0.7~1.2		
	3800		2720.0~2660.0	45.3~44.3	48.7~72.4	70.2~100.0	65	0.7~1.2		
	4000		2871.7~2808.5	47.9~46.8	51.3~76.3	69.3~98.7	65	0.7~1.2		
	4200		3024.3~2957.7	50.4~49.3	53.8~80.1	68.9~98.2	65	0.7~1.2		
	4400		3177.9~3107.9	53.0~51.8	56.4~83.9	68.6~97.7	65	0.7~1.2		
	4600		3332.3~3258.9	55.5~54.3	58.9~87.7	68.2~97.2	65	0.7~1.2		
	4800		3487.6~3410.8	58.1~56.8	61.5~91.5	67.6~96.3	65	0.7~1.2		
	1~1.5 (bar)		12bar以上 不推荐低速	II	1430.4~1398.0	23.8~23.3	47.0~65.0	121.7~154.1	65	0.7~1.2
			2600		1579.4~1543.6	26.3~25.7	50.7~70.2	119.9~151.8	65	0.7~1.2
2800		1731.8~1692.6	28.9~28.2		54.4~75.3	118.2~149.5	65	0.7~1.2		
3000		1887.6~1844.9	31.5~30.7		58.0~80.3	116.4~147.3	65	0.7~1.2		
3200		2047.0~2000.7	34.1~33.3		61.5~85.2	114.7~145.1	65	0.7~1.2		
3400		2210.0~2160.0	36.8~36.0		65.0~90.0	113.0~143.0	65	0.7~1.2		
3600		2355.2~2301.9	39.3~38.4		69.1~95.6	111.5~141.1	65	0.7~1.2		
3800		2501.2~2444.6	41.7~40.7		73.1~101.3	110.1~139.3	65	0.7~1.2		
4000		2648.1~2588.2	44.1~43.1		77.2~106.9	108.7~137.5	65	0.7~1.2		
4200		2795.8~2732.5	46.6~45.5		81.3~112.5	107.2~135.7	65	0.7~1.2		
4400		2944.4~2877.8	49.1~48.0		85.3~118.1	106.7~135.0	65	0.7~1.2		
4600		3093.9~3023.9	51.6~50.4		89.4~123.8	106.2~134.4	65	0.7~1.2		
4800		3244.2~3170.8	54.1~52.8		93.4~129.4	105.6~133.7	65	0.7~1.2		
		3395.4~3318.6	56.6~55.3		97.5~135.0	104.6~132.3	65	0.7~1.2		

Host model	LBG280RA	Intake pressure	1 atm	IAT	25°C	AT	80%R. H.			
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure		
			(m³/h)	(m³/min)	(kW)	°C	°C	bar		
0.4~0.9 (bar)	2000	I	2202~2165	36.7~36.1	42.5~638	73~107	65	0.7~1.2		
	2100		2335~2297	38.9~38.3	44.5~66.7	72~106	65	0.7~1.2		
	2200		2471~2430	41.2~40.5	46.4~69.6	71~105	65	0.7~1.2		
	2300		2609~2566	43.5~42.8	48.3~72.5	70~104	65	0.7~1.2		
	2400		2750~2705	45.8~45.1	50.2~75.4	70~102	65	0.7~1.2		
	2500		2894~2846	48.2~47.4	52.1~78.2	69~101	65	0.7~1.2		
	2600		3040~2990	50.7~49.8	54.0~81.0	68~100	65	0.7~1.2		
	2700		3173~3121	52.9~520	56.1~84.1	67~99	65	0.7~1.2		
	2800		3307~3252	55.1~54.2	58.2~87.2	67~98	65	0.7~1.2		
	2900		3442~3385	57.4~56.4	60.2~90.3	66~97	65	0.7~1.2		
	3000		3578~3520	59.6~587	62.3~93.5	65~96	65	0.7~1.2		
	3100		3716~3655	61.9~60.9	64.4~96.6	65~95	65	0.7~1.2		
	3200		3855~3792	64.3~63.2	66.5~99.7	64~94	65	0.7~1.2		
	3300		3996~3930	66.6~65.5	68.5~102.8	63~93	65	0.7~1.2		
	1~1.5 (bar)		2000	II	2158~2100	36.0~35.0	67.8~96.1	116~146	65	0.7~1.2
			2100		2289~2228	38.1~37.1	70.9~100.5	115~144	65	0.7~1.2
2200		2422~2357	40.4~393		73.9~104.9	113~143	65	0.7~1.2		
2300		2558~2489	42.6~41.5		77.0~109.2	112~141	65	0.7~1.2		
2400		2696~2624	44.9~43.7		80.0~113.5	111~139	65	0.7~1.2		
2500		2837~2761	47.3~46.0		83.0~117.8	109~138	65	0.7~1.2		
2600		2980~2900	49.7~48.3		86.0~122.0	108~136	65	0.7~1.2		
2700		3110~3027	51.8~50.4		89.3~126.7	107~135	65	0.7~1.2		
2800		3241~3154	54.0~52.6		92.6~131.4	106~133	65	0.7~1.2		
2900		3374~3283	56.2~54.7		95.9~136.1	105~132	65	0.7~1.2		
3000		3508~3414	58.5~56.9		99.2~140.8	104~131	65	0.7~1.2		
3100		3643~3545	60.7~59.1		102.5~145.5	103~129	65	0.7~1.2		
3200		3779~3678	63.0~61.3		105.8~150.2	102~128	65	0.7~1.2		
3300		3917~3812	65.3~63.5		109.2~154.8	101~127	65	0.7~1.2		

PARAMETERS AND EXHIBITION

Host model		LBG300RB		Intake pressure	1 atm	IAT	25°C	AT	80%R. H.
DISCHARGE (bar)	RPM	type	CC		Shaft power	EGT	FTT	Injection pressure	
			(m³/h)	(m³/min)	(kW)	°C	°C	bar	
0.4~0.9 (bar)	2000	I	3375~3331	56.2~55.5	66.2~104.8	73~107	65	0.7~1.2	
	2100		3579~3533	59.7~58.9	69.2~109.6	72~106	65	0.7~1.2	
	2200		3788~3739	63.1~62.3	72.2~114.3	71~105	65	0.7~1.2	
	2300		4000~3948	66.7~65.8	75.2~119.1	70~104	65	0.7~1.2	
	2400		4216~4162	70.3~69.4	78.2~123.8	70~102	65	0.7~1.2	
	2500		4436~4379	73.9~73.0	81.1~128.4	69~101	65	0.7~1.2	
	2600		4660~4600	77.7~76.7	84.0~133.0	68~100	65	0.7~1.2	
	2700		4854~4791	80.9~79.9	87.2~138.1	67~99	65	0.7~1.2	
	2800		5049~4984	84.1~83.1	90.5~143.2	67~98	65	0.7~1.2	
	2900		5245~5177	87.4~86.3	93.7~148.3	66~97	65	0.7~1.2	
	3000		5442~5372	90.7~89.5	96.9~153.5	65~96	65	0.7~1.2	
	3100		5640~5567	94.0~92.8	100.2~158.6	65~95	65	0.7~1.2	
	3200		5839~5764	97.3~96.1	103.4~163.7	64~94	65	0.7~1.2	
	3300		6040~5962	100.7~99.4	106.6~168.8	63~93	65	0.7~1.2	
1~1.5 (bar)	2000	II	3317~3252	55.3~54.2	112.7~152.1	116~146	65	0.7~1.2	
	2100		3518~3449	58.6~57.5	117.8~159.0	115~144	65	0.7~1.2	
	2200		3723~3650	62.0~60.8	122.9~165.9	113~143	65	0.7~1.2	
	2300		3931~3854	65.5~64.2	128.0~172.8	112~141	65	0.7~1.2	
	2400		4144~4062	69.1~67.7	133.1~179.6	111~139	65	0.7~1.2	
	2500		4360~4274	72.7~71.2	138.1~186.3	109~138	65	0.7~1.2	
	2600		4580~4490	76.3~74.8	143.0~193.0	108~136	65	0.7~1.2	
	2700		4770~4677	79.5~77.9	148.5~200.4	107~135	65	0.7~1.2	
	2800		4962~4864	82.7~81.1	154.0~207.8	106~133	65	0.7~1.2	
	2900		5155~5053	85.9~84.2	159.5~215.3	105~132	65	0.7~1.2	
	3000		5348~5243	89.1~87.4	165.0~222.7	104~131	65	0.7~1.2	
	3100		5543~5434	92.4~90.6	170.5~230.1	103~129	65	0.7~1.2	
	3200		5739~5626	95.7~93.8	176.0~237.5	102~128	65	0.7~1.2	
	3300		5936~5820	98.9~97.0	181.5~245.0	101~127	65	0.7~1.2	

 Oil free screw blower

